

# FLEX SERIES


PART NUM: SA-FC-CMT

## TYPHOON CLEANING MACHINE

The contact less cleaning machine can clean assembled PCB or pallet, with a special vacuum tecnology. The Typhoon heads create a high depression that remove dust or small parts from assembled boards. A consumable free technology assures always stable performances and low cost of production. Full programmable for deep cleaning; movable heads with servo motors you can create your own cycle. SCADA HMI available.


### Benefits of SA-FC-CMT:

- High cleaning performances
- No consumables parts
- Suitable for assembled PCB or pallet
- Contact less tecnolgy
- Top or Top&bottom heads
- Easy operation and maintenance
- Full programmable cleaning cycle



*Imagery for illustration purposes only. Please consult your local Seica Automation distributor for more information.*

### Layout Module



## CMT GENERAL FEATURES

<b>TRANSPORT</b>	
<b>Height:</b>	950 mm +/- 25 mm
<b>Component clearance :</b>	Top 50 mm Bottom 30 mm
<b>Lenght:</b>	1000 mm
<b>PCB edge space:</b>	Min. 3 mm
<b>Transfer direction:</b>	Left to right/Right to left
<b>Width adjustment:</b>	Manual Adjustment
<b>Fixed Rail:</b>	Front of the machine
<b>Interface:</b>	SMEMA standard
<b>SMEMA cable length:</b>	3 m

<b>PCB OR PALLET DIMENSION</b>	
<b>Length:</b>	Min. 100 mm – Max 510 mm
<b>Width:</b>	Min. 85 mm – Max 390 mm
<b>Cleaning width:</b>	400 mm
<b>Thickness:</b>	From 0.8 mm to 4.0 mm
<b>Component clearance:</b>	Top: 50 mm - Bottom: 30 mm
<b>PCB Max. weight:</b>	2 kg
<b>Optional Cleaning width:</b>	Up to 600 mm on request

### VARIOUS:

- CE safety compliant
- Omron PLC driven system
- HMI color touch screen or SCADA as option
- Automatic width adjustment as option
- Controlled suction unit
- Available Top or Top&Bottom

### POWER SUPPLY:

230 V 1Ph+G 50Hz

### CURRENT:

4 Ampere

### AIR SUPPLY:

0,6 Mpa (2000NI/min)

### WEIGHT:

280 Kg

### DIMENSION LxWxH:

1000 x 1100 x 1320mm

### COLOR:

RAL 7035

*All modules have ESD safe design and CE mark, each module has independent control system. Technical specification may change without any advice, please contact our representative office.*

